REMOTE CONTROL DEVICE CAPABLE OF SENSING

MOTION

BACKGROUND

5 **[1001]** The present disclosure generally relates to remote control devices, and more specifically, to remote control devices capable of sensing motion.

[1002] Remote control devices are widely used for controlling the operation of electronic devices, such as

10 household electronic appliances, from a location remote from the electronic devices. Examples of electronic devices may include television, video camera recorder (VCR), and audio equipment, such as a CD player and/or a stereo system. Such remote control devices often transmit

15 operational signals by wireless radio transmission, for example, an infrared signal.

[1003] The conventional remote control device controls such functions of the electronic devices as ON/OFF state, channel selection, volume control, play, fast-forward,

20 rewind, and other functions. The remote control device provides convenience of effectuating these functions

without having to physically move to the electronic device every time it is desired to change the state of the function. Therefore, the remote control device allows the user to remotely change or select the state of the device

5 function.

[1004] However, functions and devices that may be controlled by such a conventional remote control device are often limited in terms of complexity and use. Integration of electronic devices (*e.g.*, television and audio

10 equipment) with computers and computing devices increases the need for a remote control device that can select item(s) on a display or screen that is interfacing with the integrated electronic device/computer system by sensing the motion of the control device.

15 [1005] A mouse or mouse-like device is typically used with a computer display. However, the mouse device is also limited in that it needs a flat surface to operate, and is often limited by the need for a wire connection to the computer.

20 [1006] Remote control devices with a joystick on top are known. However, these conventional devices are limiting because they can select only a limited number of pre-

defined items on the screen. Furthermore, since the joystick on the remote control device is designed to be controlled by a thumb or finger, sensitivity and accuracy of item selection can be significantly degraded.

5 [1007] In terms of reducing repetitive motion injury (e.g., carpal tunnel syndrome), it is well known that using forearm to make motions for item selections on the screen causes less injury than using wrist or finger. Thus, to alleviate the repetitive motion injury problem, attempts

10 have been made to use gyroscopes in the remote control device to sense the movement of forearm. However, gyroscopes can be cumbersome to use, bulky, and expensive.

[1008] Accordingly, there is a need for an enhanced remote control device that can sense motion but without the above-

15 described limitations of the conventional remote control devices.

SUMMARY

[1009] A remote control device includes a processor and at

20 least first and second sensors, which are operatively configured to provide position information of at least first and second points, respectively, on the remote

control device. The provided position information is

sufficiently accurate to distinguish the first point from

the second point, such that the provided position

information of the first point with respect to the position

5   information of the second point provides enough information

to the processor to determine yaw, pitch, horizontal and

vertical translation motions of the remote control device

with respect to a terrestrial plane.

[1010] In one aspect, the sensors are configured with a

10   pair of antennas and a differential GPS receiver. The

processor includes a motion converter that converts the

position information of the first and second points into

the yaw, pitch, horizontal and vertical translation motions

of the remote control device with respect to the

15   terrestrial plane. The processor also includes a cursor

movement converter that converts the processed yaw, pitch,

horizontal and vertical translation motions into a cursor

movement on a screen.

In another aspect, a method for controlling a

20   graphical icon on a screen using a remote control device is

described. The method includes determining position

information of at least two points on the remote control

device sufficiently accurate to distinguish the two points.
The position information is resolved into yaw, pitch,
horizontal and vertical translation motions, and the
resolved motions are then converted into movement

5   information of the graphical icon.

BRIEF DESCRIPTION OF THE DRAWINGS

[1011] Different aspects of the disclosure will be
described in reference to the accompanying drawings.

10   [1012] Figure 1A shows a perspective view of a remote
control device performing a yaw motion.

[1013] Figure 1B illustrates the horizontal movement of a
cursor on a computer screen in response to the yaw motion
of the remote control device.

15   [1014] Figure 2A shows a perspective view of a remote
control device performing a horizontal translation motion.

[1015] Figure 2B illustrates the horizontal movement of a
cursor on a computer screen in response to the horizontal
translation motion of the remote control device.

20   [1016] Figure 3A shows a perspective view of a remote
control device performing a pitch motion.

[1017] Figure 3B illustrates the vertical movement of a cursor on a computer screen in response to the pitch motion of the remote control device.

[1018] Figure 3C shows a side view of the remote control device illustrating the pitch motion.

[1019] Figure 4A shows a perspective view of a remote control device performing a vertical translation motion.

[1020] Figure 4B illustrates the vertical movement of a cursor on a computer screen in response to the vertical translation motion.

[1021] Figure 4C shows a side view of the remote control device illustrating the vertical translation motion.

[1022] Figure 5 shows a front view of an exemplary remote control device according to an embodiment of the present invention.

[1023] Figure 6 is a block diagram of a remote control device according to an embodiment of the present invention.

[1024] Figure 7 illustrates a configuration of position sensors as a pair of antennas and a differential GPS in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

[1025] To meet the need for an enhanced remote control device that can sense motion but without the limitations of the conventional remote control devices, exemplary embodiments are described for a remote control device that can sense four degrees of freedom motions, which include a yaw motion, a pitch motion, a horizontal translation motion, and a vertical translation motion. The yaw and horizontal translation motions cause the cursor to move horizontally on the screen, while the pitch and vertical translation motions cause the cursor to move vertically.

[1026] Figure 1A shows a perspective view of a remote control device 100 in accordance with an embodiment of the present invention. In the illustrated embodiment of Figure 1A, the remote control device 100 is shown in a configuration in which the device makes a "yaw" movement 102. The "yaw" movement 102 is defined in this specification as a horizontal angular movement of a point 104 on the remote control device 100 with respect to another point 106 on the remote control device. The horizontal plane on which the angular movement is measured is defined as a terrestrial horizontal plane. For typical

remote control purposes, the terrestrial horizontal plane is substantially parallel with "horizon" or a flat surface on earth. Thus, the yaw movement 102 will move a cursor 122 horizontally on the screen 120 (that is placed "level"

5   on a flat surface) as shown in Figure 1B. The amount or distance of the cursor movement depends on the angle of the yaw movement 102.

[1027] To be compatible with the conventional definition of "yaw" used for aircraft motion, the point 104 should be in

10   front of the point 106 with respect to the perspective of the user, who is present behind the point 106. Thus, a line from the point 106 to the point 104 will typically be pointing toward the screen 120. However, the direction will be reversed in an unusual situation when the user's

15   back is facing the screen 120.

[1028] Figure 2A shows another configuration in which the remote control device 100 makes a horizontal translation movement 202. The horizontal translation movement 202 is defined in this specification as a horizontal movement of a

20   line 108 connecting the point 104 with the point 106 with respect to the terrestrial horizontal plane. Thus, the horizontal translation movement 202 will move a cursor 222

horizontally on the screen 120 as shown in Figure 2B. The amount or distance of the cursor movement depends on the distance or length of the translation movement 202.

[1029] Figure 3A shows another configuration of the remote control device 100 in which the device makes a "pitch" movement 302. The "pitch" movement 302 is defined in this specification as a vertical angular movement of the point 104 with respect to the point 106 on the remote control device. Again, the vertical angular movement is measured with respect to the terrestrial horizontal plane. Thus, the pitch movement 302 will move a cursor 322 vertically on the screen 120 as shown in Figure 3B.

[1030] Figure 3C shows a side view of the remote control device 100 illustrating the pitch movement 302. The amount or distance of the vertical cursor movement depends on the angle of the pitch movement 302.

[1031] Figure 4A shows another configuration in which the remote control device 100 makes a vertical translation movement 402. The vertical translation movement 202 is defined in this specification as a vertical movement of the line 108 connecting the point 104 with the point 106. The vertical movement is defined as a movement along a plane

that is perpendicular to the terrestrial horizontal plane.
Thus, the vertical translation movement 402 will move a
cursor 422 vertically on the screen 120 as shown in Figure
4B. The amount or distance of the cursor movement depends

5 on the distance or length of the vertical translation
movement 402. Figure 4C shows a side view of the remote
control device 100 illustrating the vertical translation
movement 402.

[1032] Figure 5 shows a front view of an exemplary remote

10 control device 500 according to an embodiment of the
present invention. Figure 5 also illustrates a block
diagram of an external device 520 and a screen 522 that
interfaces with the external device. In one embodiment,
the external device 520 is a computer. In another

15 embodiment, the external device is a television. The
remote control device 500 is used to control a graphical
icon or cursor on the screen 522. The remote control
device 500 can be used to control displays for electronic
devices other than a computer or television.

20 [1033] In the illustrated embodiment of Figure 5, the
remote control device 500 includes a local display 502 and
various function keys and buttons 504. The remote control

device 500 also includes an antenna 506, which is used to transmit or receive radio frequency signals to and from the external device 520. The remote control device 500 may also include a CD or disk drive 508. In illustrated

5 embodiment, the drive 508 is a CD ROM drive.

[1034] The exemplary remote control device 500 also includes a pair of position sensors 510, 512, which are operatively configured so that the sensors 510, 512 can sense the motions (*i.e.*, yaw, pitch, horizontal

10 translation, and vertical translation motions) of an imaginary line 514, as described above. The motions of the line 514 are measured with respect to the terrestrial horizontal plane. Thus, various motions of the remote control device 500 are visually fed back to a user by the

15 graphical icon or cursor displayed on the screen 522. Movement of a cursor on the screen 522 copies the motions of the remote control device 500. Thus, yaw, pitch, horizontal translation, and vertical translation motions are combined and processed to produce a resultant movement

20 of the cursor on the screen 522, which is level positioned on a flat surface of the earth. If the screen 522 is positioned at an angle rather than level on a flat surface,

then this information should be entered into the remote

control device 500 to account for the tilt and

appropriately offset the movement of the cursor. The

processor 502 can appropriately calculate the offset of the

5 cursor movement.

[1035] A block diagram of a remote control device 600

according to an embodiment of the present invention is

shown in Figure 6. The remote control device 600 comprises

a main processor 602 and at least first and second sensors

10 620. The sensors 620 are operatively configured to provide

position information of at least first and second

positions, such as 104 and 106 on the remote control device

100 in Figure 1A through Figure 4A. The position

information provided by the sensors 620 should be

15 sufficiently accurate to distinguish the first position

(e.g., position 104) from the second position (e.g.,

position 106), such that the provided position information

of the first position with respect to the second position

provides enough information to the processor 602 to

20 determine yaw, pitch, horizontal and vertical translation

motions of the remote control device.

[1036] In the illustrated embodiment of Figure 6, the main processor 602 interfaces with an I/O processor 604 and a memory 606. The I/O processor 604 processes and controls a local display 612 and the sensors 620. The local display 612 can be used to display local information such as estimated motions of the remote control device with respect to the terrestrial plane and the resultant cursor movement. The display 612 can also show information such as cursor offset, position information of the remote control device, and other related information.

[1037] The main processor 602 receives the position information of the first and second positions. The main processor 602 includes a motion converter 630 that processes the position information to determine angle and distance of the yaw, pitch, horizontal and vertical translation motions. The processor 602 also includes a cursor movement converter 632 which converts these motions into an amount of cursor movement on the main screen. The main processor 602 interfaces with external devices (e.g., a computer 520 shown in Figure 5) through a transceiver 608 and an antenna 610. Thus, the amount of cursor movement is transmitted to an external device through the transceiver

608. The transceiver 608 also receives commands and messages from the external device. In some embodiments, the main processor 602 and the I/O processor 604 may be configured as one processor performing both functions.

5 [1038] In the illustrated embodiment of Figure 6, the sensors 620 are configured as position sensors rather than as attitude sensors, such as a gyroscope, for sensing the motions of the remote control device 600 because position sensors are cheaper and easier to maintain than the

10 attitude sensors. However, the use of position sensors 620 requires the sensors to be sufficiently accurate so that the movement of at least two points on the remote control device with respect to the terrestrial horizontal plane can be ascertained.

15 [1039] For example, a typical conventional remote control device that controls electronic devices, such as a television, may be about 15 to 20 centimeters long and about 4 to 6 centimeters wide. If the dimensions of the remote control device 500 shown in Figure 5 is assumed to

20 be approximately similar to the conventional remote control device, and it is assumed that the sensors would be placed longitudinally at the ends of the remote control device

500, then the accuracy of the sensors 620 should be within about 5 to 7 centimeters in order to sufficiently accurately determine the movement of the line between the two points with respect to the terrestrial horizontal

5   plane.

[1040] With the advent of Global Positioning System (GPS), terrestrial navigation has been made possible with position accuracy in the range of about one to two meters. This still is not sufficient to distinguish the positions of

10   points within a remote control device, whose dimensions are as described above. The main source of errors that contribute to degradation of GPS accuracy to this range is the timing errors. Accordingly, if the timing errors can be sufficiently corrected, the position accuracy of the GPS

15   measurement would improve significantly. A concept referred to as "differential GPS" has been used to improve the GPS accuracy by significantly reducing the timing errors. Accordingly, it was realized that the use of a differential GPS receiver with antennas strategically

20   placed on the remote control device can provide terrestrial positions with sufficient accuracy (i.e., within about 5 to

7 centimeters) to enable motion sensing within the remote control device.

[1041] Figure 7 illustrates a configuration of position sensors as a pair of antennas and a differential GPS in accordance with an embodiment of the present invention. Various function keys and buttons have been omitted for clarity.

[1042] In the illustrated embodiment of Figure 7, the remote control device 700 includes sensors, which are configured as a pair of antennas 702, 704 and a differential GPS receiver 706. The antenna 702 provides received GPS signal at a position where the antenna 702 is located. Likewise, the antenna 704 provides received GPS signal at a position where the antenna 704 is located. The differential GPS receiver 706 receives the signals from the two antennas 702, 704, along with corrections necessary to substantially reduce the timing errors. In an alternative embodiment, the sensors can be configured as a plurality of antennas and a corresponding plurality of differential GPS receivers.

[1043] In one embodiment, the corrections can be received from a source through a transceiver on the remote control

-16-

device. The source may be an Internet site that provides the corrections when the approximate location of the remote control device is entered. In another embodiment, the corrections can be locally broadcast to the transceiver.

5 In a further embodiment, the corrections can be calculated by the differential GPS receiver 706 by providing sufficiently accurate position information of the relatively stationary remote control device 700.

[1044] While specific embodiments of the invention have

10 been illustrated and described, other embodiments and variations are possible. Although the position sensors have been presented as being configured as a differential GPS receiver with two antennas, other position sensors, available now or in the future, that can provide similar

15 position accuracy of the points on the remote control device are contemplated. For example, the position sensors can be relative sensors that constantly measure the 3-dimensional position of the remote control device with respect to a fixed position such as a top corner of a main

20 display.

[1045] All these are intended to be encompassed by the following claims.